



TUHI K1-1212 CNC Router Manual toolchange

POA



5.5kW high-efficiency dry-vane vacuum pump



6kW ER32 collet spindle

STANDARD FEATURES

1220 x 1220 x 200mm work envelope, overall dimensions 2000W x 2800L x 2100mmH, 1500kgs
6kW 18000rpm HSD electric fan cooled manual collet spindle, ER32 collets 3-20mm
Tool length measuring system
NCStudio PM53C CNC control system, Windows computer system, PCI card.
850W Yaskawa servo motors with Motovario (France) planetary reduction gearboxes
Up to 40m/min rapid travel, 30m/min working speed.
Automatic lubricant system to linear bearings
Taiwanese rack and pinion, linear bearings and guideways
125mm dust collection port at top of Z axis, dusthood
5.5kW high-efficiency dry-vane vacuum pump, footpedal control, popup stops
Cost includes delivery within main centres, basic training and installation assistance.
Add GST to all costs.

OPTIONAL UPGRADES

ADD

Safety fences	\$2500
Safety light curtain	\$1750
300mm gantry clearance, 500mm travel	\$2500
9kW auto-toolchange spindle & linear rack	\$13675
Mecsoft VisualCAM XPress Software	\$850
VisualCAM STD	\$2550
3hp cyclone extraction system	\$3850



